








SPECIFICATION / DW Contract Axminster

Construction:	Woven Gripper Axminster – 7 pitch
Type:	Cut Pile
Pile material:	80 % Pure New Wool 20 % Antistatic Polyamide Type 6.6, 3 ply
Colour / Design:	Pre dyed yarn, up to 7 colours – No design limitations
Width:	100-200-300-366-400 cm
Weft:	100 % Polypropylene
Warp:	50 % Cotton / 50 % Polyester

Construction	Fire Classifications
 <p>7Pitch Gripper Axminster</p>	 DNV 0575 IMO FPT Code part 2 and 5  Russian fire Certificate  CE  EN 14041-Class Cfl-s1

Pile Weight	Density	Pile Height	Total Height	Total Weight	Luxury Rating Class	Overall Classification	Use Intensity
1300	7	7.5	10	2250	LC 4 	Class 32	Commercial General 
1500	8	7.5	10	2270	LC 5 	Class 33	Commercial Heavy 
1700	9	7.5	10	2530	LC 5 	Class 33	Commercial Heavy 
1900	10	7.5	10	2650	LC 5 	Class 33	Commercial Heavy 
2100	10	9	12	2850	LC 5 	Class 33	Commercial Heavy 
2300	10	10	13	3050	LC 5 	Class 33	Commercial Heavy 

Density: Measured in rows/inch. Indicate number of tufts per inch

Pile height: Indicate the height in mm of the pile above the substrate. EN ISO 1766

Pile weight: Conditioned yarn weight in g/m², woven into the carpet
Tolerance –10% +15%.

Total carpet weight: Indicate the total weight in g/m² of the finished carpet.
Tolerance according to EN 1307 standards: +/- 15 %

Test methods and Tolerances: Referring to: European Norm of Textile floor coverings – Classification of pile carpet EN 1307, 2005.
Requirement for tolerances on dimensions of wall-to-wall carpet and pattern repeat: 14159 CEN/TS

Opdateret 8. januar 2015