







SPECIFICATION / DW Contract ColorTec / 500g

Construction:	Tufted ColorTec – 7 pitch
Type:	Cut Pile
Pile material:	80 % Pure New Wool 20 % Antistatic Polyamide Type 6.6, 2 and 3 ply
Colour / Design:	Pre dyed yarn, up to 6 colours – No design limitations
Width:	400-500 cm – possibility to split production rolls into 2x200 cm and 2x250 cm width
Backing:	Felt 500g Polyester / Polyamide Laminated to the carpet with a propylene film

Construction	Fire Classifications
 <p>7 Pitch tufted ColorTec</p>	 DNV 0575 IMO FPT Code part 2 and 5  2531-CPR-CXA10121  EN 14041-Class Cfl-s1

Pile Weight	Density 2/3 ply	Pile Height	Total Height	Total Weight	Luxury Rating Class	Overall Classification	Use Intensity
1100	9/-	7.5	13	2130/1900	LC 3 	Class 32	Commercial General 
1300	10/-	7.5	13	2330/2100	LC 4 	Class 32	Commercial General 
1500	12/-	7.5	13	2530/2300	LC 5 	Class 33	Commercial Heavy 
1700	14/9	7.5	13	2730/2500	LC 5 	Class 33	Commercial Heavy 
1800	15/9,5	7.5	13	2830/2600	LC 5 	Class 33	Commercial Heavy 
1900	-/10	7.5	13	2930/2700	LC 5 	Class 33	Commercial Heavy 

Density:	Measured in rows/inch. Indicate number of tufts per inch
Pile height:	Indicate the height in mm of the pile above the substrate. EN ISO 1766
Pile weight:	Conditioned yarn weight in g/m ² , tufted into the carpet Tolerance -10% +15%.
Total weight:	Indicate the total weight in g/m ² of the finished carpet. Tolerance according to EN 1307 standards: +/- 15 % Conditioned yarn weight/unconditioned yarn weight

Test methods and Tolerances: Referring to: European Norm of Textile floor coverings – Classification of pile carpet EN 1307, 2008. Requirement for tolerances on dimensions of wall-to-wall carpet and pattern repeat: 14159 CEN/TS

Opdateret 19.august 2015