

**CERTIFICATE OF CONSTANCY OF PERFORMANCE**

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Product group 2**

for application as flooring,

produced by or for

**Dansk Wilton A/S  
Højskolevej 3, Birk  
DK-7400 Herning**

and produced in the manufacturing plant (s)

**CXA10122**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

**EN 14041:2004 : Resilient, textile and laminate floor coverings – Essential  
EN 14041:2004/AC:2006 characteristics**

under system 1 are applied and that the product fulfils (products fulfil) the essential characteristic of **reaction to fire: Class C<sub>fl</sub>-s1.**

The attached 2 annexes forms part of this certificate.

This certificate was issued on **2014-08-01** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonized standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

(This certificate supersedes the previous version of this certificate, issued 2012-07-25 by NB 0845.)



Tom Nisted



Merete Poulsen

The certificate should only be reproduced extenso  
– in extracts only with a written agreement with DBI Certification A/S.

**DBI Certification A/S**

Jernholmen 12, 2650 Hvidovre  
Tlf.: 36 34 90 90

E-mail: info@dbicertification.dk  
www.dbicertification.dk



**DANAK**  
Prod. Reg. Nr. 7023

Version 2014-07-30  
Page 1 of 3

**EXTENT**

<b>Type</b>	<b>Description</b>
<p>DW Contract ColorTec/Graffic 1100 gr – 1900 gr with textile</p> <p>Field of application</p>	<p>Tufted carpet with cut loop pile.</p> <p>Pile: 80 % pure new wool and 20 % polyamide, 1100 to 1900 g/m<sup>2</sup></p> <p>Rear side: textile, 108 g polypropylene</p> <p>Total height: 10 mm</p> <p>Pile height: 7.5 mm</p> <p>Total weight: 1740 to 2540 g/m<sup>2</sup></p> <p>The carpet is to be laid loose or mounted on a substrate of Euroclasses A1<sub>fl</sub> or A2<sub>fl</sub> at least 6 mm thick and with density equal to or greater than 1350 kg/m<sup>3</sup>.</p>

The certificate should only be reproduced extenso  
– in extracts only with a written agreement with DBI Certification A/S.

# Certificate No.: 2531 – CPR–CXA10122

Date: 2014-08-01



## TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
DBI	PF12563d	2007-07-16
DBI	PF12563e	2007-01-05
DBI	PC10115b	2007-07-16

## TECHNICAL BASIS

Designation	Identification	Date
Product specification DW Contract ColorTec/Graffic 1100 – 1900 g with textile		2012-07-25
Supplementary information		2012-07-25

The certificate should only be reproduced extenso  
– in extracts only with a written agreement with DBI Certification A/S.

### DBI Certification A/S

Jernholmen 12, 2650 Hvidovre  
Tlf.: 36 34 90 90

E-mail: [info@dbicertification.dk](mailto:info@dbicertification.dk)  
[www.dbicertification.dk](http://www.dbicertification.dk)

**DANAK**  
Prod. Reg. Nr. 7023

Version 2014-07-30  
Page 3 of 3