














SPECIFICATION / DW Contract Graffic / 500g

Construction:	Tufted Graffic – 8 pitch
Type:	Cut Pile
Pile material:	80 % Pure New Wool Antistatic 20 % Antistatic Polyamide Type 6.6, 2 ply
Colour / Design:	Pre dyed yarn, limited colour and design possibilities.
Width:	400-500 cm
Backing:	Felt 500g Polyester / Polyamide Laminated to the carpet with a propylene film

Construction	Fire Classifications
 <p>8 pitch tufted Graffic</p>	 DNV 0575 IMO FPT Code part 2 and 5  2531-CPR-CXA10121  EN 14041-Class Cfl-s1

Pile Weight	Density	Pile Height	Total Height	Total Weight	Luxury Rating Class	Overall Classification	Use Intensity
1100	8	6	11	2130/1900	LC 3 	Class 32	Commercial General 
1200	8	6	11	2230/2000	LC 3 	Class 32	Commercial General 
1300	12	6	11	2330/2100	LC 4 	Class 32	Commercial General 
1500	12	7	12	2530/2300	LC 4 	Class 32	Commercial General 
1700	12	8	13	2730/2500	LC 5 	Class 33	Commercial Heavy 

Density:	Measured in rows/inch. Indicate number of tufts per inch
Pile height:	Indicate the height in mm of the pile above the substrate. EN ISO 1766
Pile weight:	Conditioned yarn weight in g/m ² , tufted into the carpet Tolerance -10% +15%.
Total weight:	Indicate the total weight in g/m ² of the finished carpet. Tolerance according to EN 1307 standards: +/- 15 % Conditioned yarn weight/unconditioned yarn weight

Test methods and Tolerances:	Referring to: European Norm of Textile floor coverings – Classification of pile carpet EN 1307, 2005. Requirement for tolerances on dimensions of wall-to-wall carpet and pattern repeat: 14159 CEN/TS
-------------------------------------	---

Odateret 19. august 2015